

(11) **EP 0 817 461 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
07.01.1998 Bulletin 1998/02

(51) Int. Cl.<sup>6</sup>: **H04N 1/21**

(21) Application number: 97110402.1

(22) Date of filing: 25.06.1997

(84) Designated Contracting States:  
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE**

(30) Priority: 25.06.1996 JP 164016/96

(71) Applicant:  
**MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.**  
Kadoma-shi, Osaka-fu, 571 (JP)

(72) Inventors:  
• Hisatomi, Kenji  
Moriguchi-shi, Osaka 570 (JP)

• Yamaguchi, Takehito  
Hirakata-shi, Osaka 573 (JP)  
• Murata, Kazuyuki  
Kyotanabe-shi, Kyoto 610-03 (JP)  
• Matsukawa, Shigeru  
Hirakata-shi, Osaka 573 (JP)


(74) Representative:  
Grünecker, Kinkeldey,  
Stockmair & Schwanhäusser  
Anwaltssozietät  
Maximilianstrasse 58  
80538 München (DE)

(54) **Image information processor and image information transmitter**

(57) An image information processor has an image superimposing and outputting means for printing out a superimposed image where a bar code representative of a storage location of an electronic document file received through a facsimile is superimposed on the first page of the electronic document file. When a necessary electronic document file is read out, the bar code is read from the printed output corresponding to the

necessary electronic document file being set by the user, the storage location of the electronic document file is decrypted from the bar code to thereby identify and read out the electronic document file. In this case, the reading of the bar code is performed only when a permitted password is inputted by the user. The readout of the electronic document file is not performed otherwise.

FIG. 1



BEST AVAILABLE COPY

EP 0 817 461 A2

## Description

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to an image information processor such as an electronic filing apparatus having a means for storing electronic document data.

#### 2. Description of the Related Art

In recent years, an image information processor has been developed in which electronic document data being transmitted and received are stored as electronic document files in a storage means such as a memory and the contents in the memory can be confirmed on a display unit. For example, as shown in Japanese Laid-open Patent Application No. H4-86064, this type of image information processor has a function of storing received electronic document files in the storage means so that the stored files may be printed out by the user's operation. Therefore, the electronic document files stored in the storage means are first confirmed on the display unit for selection and then, the selected file is printed out through a printer.

FIG. 10 shows a prior art of the image information processor having a storage means. In the image information processor shown in FIG. 10, when connection to the line is made by a facsimile communication unit 801, the transmission protocol is decided by the transmitting side facsimile and a central control unit 804, and a facsimile signal is sent from the transmitting side facsimile. The facsimile signal is converted into a binary signal by a signal converting unit 802 and after indices such as the date and the identification (ID) code of the transmitting side are added, the binary data are stored in a storage unit 803. The contents in the storage unit 803 together with the indices are displayed on a display unit 806 by operating an operation unit 807. Looking at the display, the user determines whether the received data are necessary or not, and prints out only necessary documents onto recording paper through a printer unit 805 by operating the operation unit 7. The unnecessary documents are erased from the storage unit 803 without being printed out.

Moreover, as shown in Japanese Laid-open Patent Application H6-217045, the image information processor may be arranged so that the electronic document files being stored are displayed on a display terminal to perform a search and the selected electronic document file stored in the storage means is transmitted together with image information of an attached document being read in. FIG. 11 shows a prior art of the image information processor having a storage means. In a facsimile apparatus having a reading means 902 for reading the character image of an attached document being set and a storage means 909 for storing electronic document

data, the following means are provided: a detection means 901 for detecting the presence/absence of the attached document being set on the reading means 902; and a control means for controlling so that when the detection means 901 detects the presence of the attached document, the electronic document data read by the reading means 902 are also transmitted in transmitting the electronic document data stored in the storage means 909. A facsimile cover sheet which is the attached document being set on the storage means 902 and the electronic document data stored in the storage means 909 can be transmitted together to another facsimile.

Moreover, as shown in Japanese Laid-open Patent Application No. S62-157471, the image information processor may have a simple confidential reception function which enables communications respecting each receiver's privacy so that only the receiver's name and the file number are outputted onto the recording paper at the time of facsimile reception and only the facsimile-received document of the specified file number is outputted in taking out facsimile-received documents. FIG. 12 shows a prior art of the image information processor having a storage means. In the prior art, when a confidential reception mode is set by an operation button of an operation display unit 1003, the facsimile performs a receiving operation in the following manner: When a document to be transmitted is set on a transmitting side facsimile (hereinafter, referred to as transmitting station) and transmission is started, on the receiving side, a network controller 1010 senses a call signal and performs switching from the telephone section to the main section of the apparatus. A system control unit 1001 causes a file number generating unit 1004 to generate a file number and stores the file number in an image memory 1002 so that facsimile-received documents are successively stored in the memory area corresponding to the file number. At a plotter 1008, recording paper is outputted having a width D where only the receiver's name entered on the transmitting side and a file number Fno recorded by the facsimile are shown.

In the image information processor, however, when selection is made from among the electronic document files being stored, it is necessary to display the electronic document files on the display screen and perform a search to make a decision. Therefore, as the number of stored electronic document files increases, the search becomes more complicated and requires are time. Additionally, the provision of the display unit such as the display screen for displaying the details of the images increases the cost.

Further, when an electronic document file is facsimile-transmitted together with an attached document, it is necessary to follow a complicated procedure such that after the electronic document file is searched for and the attached document is read in, both are correlated.

Moreover, in inputting from the keyboard a number

outputted when a received document stored in the storage means is taken out, there is a risk of input error.

#### SUMMARY OF THE INVENTION

In view of the above-mentioned problems of the prior arts, an object of the present invention is to provide an image information processor and an image information communication apparatus where the identification of electronic document files stored in the storage means such as a memory is more easily performed.

In order to achieve the above-mentioned object, the present invention of an image information processor comprises: storage means for storing a plurality of electronic document files; image superimposing and outputting means for superimposing identification information for identifying a predetermined electronic document file stored in the storage means on image information of a specific page of the predetermined electronic document file, and printing out the superimposed image; and readout means for reading a printed output of the superimposed image, reading the identification information included in the superimposed image, and reading a corresponding electronic document file from the storage means based on the file identification information,

wherein when an attached document is read in together with the printed output of the superimposed image, the readout means makes a distinction between the printed output of the superimposed image and the attached document by use of the identification information.

The present invention of an image information processor comprises: storage means for storing a plurality of electronic document files; image superimposing and outputting means for superimposing identification information for identifying a predetermined electronic document file stored in the storage means on image information of a specific page of the predetermined electronic document file, and printing out the superimposed image; readout means for reading a printed output of the superimposed image, reading the identification information included in the superimposed image, and reading a corresponding electronic document file from the storage means based on the file identification information; and facsimile reception means for receiving data transmitted from a facsimile,

wherein the plurality of electronic document files stored in the storage means include a file received by the facsimile reception means.

The present invention of an image information processor comprises: storage means for storing a plurality of electronic document files; image superimposing and outputting means for superimposing identification information for identifying a predetermined electronic document file stored in the storage means on image information of a specific page of the predetermined electronic document file, and printing out the superimposed image; and readout means for reading a printed

output of the superimposed image, reading the identification information included in the superimposed image, and reading a corresponding electronic document file from the storage means based on the file identification information,

wherein said readout means collates input password information being inputted with previously-recorded use permission information, and reads out an electronic document file being stored only when both of the information coincide with each other.

The present invention of an image information processor comprises: storage means for storing a plurality of electronic document files; image superimposing and outputting means for superimposing identification information for identifying a predetermined electronic document file stored in the storage means on image information of a specific page of the predetermined electronic document file, and printing out the superimposed image; readout means for reading a printed output where the superimposed image is shown, reading the identification information included in the superimposed image, and reading a corresponding electronic document file from the storage means based on the file identification information; facsimile communication means for transmitting and receiving according to a facsimile format the electronic document file read out by the readout means; transmission error message generating and outputting means for adding at least receiver information for identifying a receiver of an electronic document file whose transmission resulted in error and identification information for identifying the electronic document file to a medium on which a transmission error message is shown, said medium being outputted when a transmission error occurs during transmission according to the facsimile format; and re-transmission control means for, when re-transmission according to the facsimile format is directed, causing the facsimile communication means to re-transmit the electronic document file whose transmission resulted in error by using at least the receiver information and the identification information added to the medium being outputted.

The present invention of an image information communication apparatus comprises: facsimile communication means for transmitting and receiving image information according to a facsimile format; re-transmission information generating means for, when a transmission error occurs during transmission according to the facsimile format, generating, together with a transmission error message, re-transmission information including receiver information for identifying a receiver of the facsimile transmission and information for identifying image information whose transmission resulted in error; and re-transmission control means for, when re-transmission according to the facsimile format is directed, causing the facsimile communication means to re-transmit the image information whose transmission resulted in error by using the re-transmission information being generated.

According to the present invention, in an image information processor having storage means for storing an electronic document file, for example, file storage location information of the electronic document file is printed out onto a sheet of paper together with the image of the first page, and in identifying the electronic document file, the printed sheet is read in and the file storage location information is obtained to thereby take out a desired electronic document file.

Moreover, in reading the image of the storage location information of the electronic document file, the document to be transmitted is also read in and facsimile-transmitted together with the electronic document file, for example, to the same receiver.

Inputted use permission information is collated with previously-recorded use permission information and only when both coincide with each other, the facsimile-received document, for example, is printed out.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows the structure of an image information processor according to embodiments of the present invention;

FIG. 2 is a flowchart of an embodiment of the present invention;

FIG. 3A is a flowchart of an embodiment of the present invention;

FIG. 3B is a flowchart of the embodiment of the present invention;

FIG. 4 is a flowchart of an embodiment of the present invention;

FIG. 5A is a flowchart of an embodiment of the present invention;

FIG. 5B is a flowchart of the embodiment of the present invention;

FIG. 6 shows an example of a printed output of a bar code corresponding to a file according to the present invention;

FIG. 7 shows an example of a printed output of a superimposed image according to the present invention;

FIG. 8 is a flowchart of an embodiment of the present invention;

FIG. 9 shows a transmission error report sheet according to an embodiment of the present invention;

FIG. 10 schematically shows the structure of a conventional electronic filing apparatus;

FIG. 11 schematically shows the structure of another conventional electronic filing apparatus; and

FIG. 12 schematically shows the structure of another conventional electronic filing apparatus.

#### Description of the Reference Designations

101 CPU

102	ROM
103	RAM
104	IMAGE-ONLY RAM
105	SYSTEM BUS
106	HDD
107	HDD I/F
108	KEYBOARD
109	KEYBOARD I/F
110	IMAGE READER
111	IMAGE READER I/F
112	IMAGE PRINTER
113	IMAGE PRINTER I/F
114	FACSIMILE RECEIVER
115	FACSIMILE RECEIVER I/F
116	FACSIMILE TRANSMITTER
117	FACSIMILE TRANSMITTER I/F
801	FACSIMILE COMMUNICATION UNIT
802	SIGNAL CONVERTING UNIT
803	STORAGE UNIT
804	CENTRAL CONTROL UNIT
805	PRINTER UNIT
806	DISPLAY UNIT
807	OPERATION UNIT
901	SCANNER
902	DISPLAY
903	KEYBOARD
904	COMMUNICATION APPARATUS
905	DOCUMENT DETECTION SENSOR
906	SCANNER CONTROL UNIT
907	DISPLAY CONTROL UNIT
908	KEY CONTROL UNIT
909	MEMORY UNIT
910	COMMUNICATION APPARATUS CONTROL UNIT
911	CONTROL UNIT
1001	SYSTEM CONTROL UNIT
1002	COMMUNICATION MEMORY
1003	OPERATION DISPLAY UNIT
1004	FILE NUMBER GENERATING UNIT
1005	COMMUNICATION CONTROL UNIT
1006	CODING/DECODING UNIT
1007	SCANNER
1008	PLOTTER
1009	MODEM
1010	NETWORK CONTROLLER

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, embodiments of the present invention will be described with reference to the drawings.

Referring to FIG. 1, an image information processor according to the embodiments of the present invention includes a central processing unit (CPU) 101 which is a microprocessor serving as a control means, a read only memory (ROM) 102 normally storing a program which defines operation procedures of the CPU 101, a random access memory (RAM) 103 for temporarily storing set

information which RAM 103 also serves as the work area of the CPU 101, an image-only RAM 104 for storing images, a system bus 105 for connecting devices, a hard disk drive (HDD) 106 for holding electronic document files, a keyboard 108 serving as a user's instruction inputting means, an image reader 110 for reading images, an image printer 112 for printing images, a facsimile receiver 114 for performing a facsimile reception processing, and a facsimile transmitter 116 for performing a facsimile transmission processing. The image information processor further includes an HDD interface (I/F) 107 for connecting the HDD 106 and the system bus 105, a keyboard I/F 109 for connecting the keyboard 108 and the system bus 105, an image reader I/F 111 for connecting the image reader 110 and the system bus 105, an image printer I/F 113 for connecting the image printer 112 and the system bus 105, a facsimile receiver I/F 115 for connecting the facsimile receiver 114 and the system bus 105, and a facsimile transmitter I/F 117 for connecting the facsimile transmitter 116 and the system bus 105. FIG. 1 shows the structure of the embodiment.

Subsequently, an operation procedure of a first embodiment will be described with reference to the structural view of FIG. 1 and the flowchart shown in FIG. 2.

The image read by the image reader 110 (201) is stored on the HDD 106 as an electronic document file by the CPU 101 (202). The CPU 101 reads out the file name of the electronic document file as storage location information, converts it into a bar code (203) and places it on the RAM 103. The bar code may be a character string. Then, the CPU 101 takes out the first page of the image being read out and places it on the image-only RAM 104. Then, the CPU 101 superimposes the bar code on the image of the cover page to form a superimposed image and places it on the image-only RAM 104 (204). Then, the CPU 101 reads out the superimposed image from the image-only RAM 104 and prints it out through the image printer 112 (205). An example of the printed output is shown in FIG. 6.

In performing facsimile transmission by taking out a file on the HDD 106 (206), the user selects the printed output of the superimposed image corresponding to the file to be transmitted and reads it in with the image reader 110 (207). The superimposed image being read in is placed on the image-only RAM 104 and the CPU 101 cuts out the bar code from the superimposed image (208), obtains the file storage location information from the bar code (209), takes out a file corresponding to the bar code based on the information and places the file on the image-only RAM 104 (210). From the keyboard 108, the user commands the CPU 101 to perform facsimile transmission (211) and the CPU 101 transmits the file on the image-only RAM 104 from the facsimile transmitter 116 (212).

Subsequently, an operation procedure of a second embodiment will be described with reference to the

structural view of FIG. 1 and the flowcharts of FIGs. 3A and 3B. The structure of the image information processor of this embodiment will not be described because it is basically the same as that of FIG. 1.

Steps 301 to 305 as shown in Fig. 3A are similar to steps 201 to 205 as shown in Fig. 2.

At step 206 of the operation procedure of the first embodiment, in reading in the printed superimposed image with the image reader 110 to take out a desired file from the HDD 106 (306), the user reads in a document to be attached with the image reader 110 (307). The superimposed image and the attached document being read in are placed on the image-only RAM 104 and transmitted to the CPU 101 every image corresponding to one page. The CPU 101 determines whether the image is a superimposed image or an attached document based on whether the bar code is included or not (308). When the image is not a superimposed image, it is left on the image-only RAM 104 because it is an attached document (313). When the image is a superimposed image, the CPU 101 cuts out the bar code from the superimposed image (309), obtains file storage location information from the bar code (310), takes out a desired file from the HDD 106 based on the information and places the file on the image-only RAM 104 (312). These operations are finished when they have been performed for all the documents being read in (314).

Then, from the keyboard 108, the user commands the CPU 101 to perform facsimile transmission (315), and the CPU 101 transmits through the facsimile transmitter 116 the desired file data on the image-only RAM 104 together with the attached document data (316). This enables the user to facsimile-transmit an electronic document file together with an attached document to the same receiver without any need to search the HDD 106 for the file. The bar code may be a character string.

Subsequently, an operation procedure of a third embodiment will be described with reference to the structural view of FIG. 1 and the flowchart of FIG. 4. The structure of the image information processor of this embodiment will not be described because it is basically the same as that of FIG. 1.

The document received by the facsimile receiver 114 (401) is stored on the HDD 106 by the CPU 101 (402). The CPU 101 reads out storage location information of the received document file on the HDD 106, converts the information into a bar code and places it on the RAM 103 (403). The bar code may be a character string. Then, the CPU 101 takes out the image of the cover page or the first page of the received document file and places it on the image-only RAM 104. The CPU 101 superimposes the bar code on the RAM 103 on the image of the cover page on the image-only RAM 104 (404) and prints it out through the image printer 112 (405). An example of the printed output is shown in FIG. 7.

When the user looks at the printed superimposed

image to take out the received document file on the HDD 106 and prints it out (406), the user reads in the printed superimposed image with the image reader 110 (407). The superimposed image being read in is placed on the image-only RAM 104. The CPU 101 cuts out the bar code from the superimposed image (408), obtains file storage location information from the bar code (409), takes out the received document file from the HDD 106 based on the information and places it on the image-only RAM 104 (410). Then, the CPU 101 prints out the received document file on the image-only RAM 104 through the image printer 112 (411). Since only the cover page or the first page of the received document is automatically outputted and the remaining received pages may be taken out by reading in the superimposed image, the simple confidential reception function is realized. In addition, the received document is easily printed out without any need to search the HDD 106 storing a number of received document files for a desired document.

Subsequently, an operation procedure of a fourth embodiment will be described with reference to the structural view of FIG. 1 and the flowchart of FIGS. 5A and 5B. The structure of the image information processor of this embodiment will not be described because it is basically the same as that of FIG. 1.

Steps 501 to 505 as shown in Fig. 5A and steps 512 to 516 as shown in Fig. 5B are similar to steps 401 to 405 and 407 to 411, respectively, as shown in Fig. 4.

In the third embodiment, the person in charge of the apparatus previously creates a password table which only the persons permitted to use the apparatus know (506) and stores the password table in the ROM 102 (507). Before reading in the printed superimposed image with the image reader 110, the user inputs a keyword as the password from the keyboard 108 (509). The CPU 101 places the inputted keyword on the RAM 103, compares the keyword with the password on the ROM 102 (510) and permits the readout with the image reader 110 when the keyword coincides with the password. Instead of inputting the keyword from the keyboard, the keyword may be inputted by inserting a magnetic card having the keyword written thereon into a magnetic card reader. Moreover, the same result is obtained by inserting an integrated circuit (IC) card having the keyword written thereon into an IC card reader. Since even if the user tries to take out the received document by use of the paper on which the superimposed image is printed out, the received document cannot be taken out unless the user is permitted to use the apparatus, the simple confidential reception function is realized.

Subsequently, an operation procedure of a fifth embodiment will be described with reference to the structural view of FIG. 1 and the flowchart of FIG. 8.

An electronic file originally recorded on the HDD 106 or read out by the image reader 110 and recorded on the HDD 106 or the RAM 103 is facsimile-transmitted

through the facsimile transmitter 116 (1101). When a transmission error occurs during the transmission (1102), the CPU 101 stores the file storage location information and transmission conditions such as the receiver's facsimile number 1201 and the date of transmission 1202 in the RAM 103 or the HDD 106 as re-transmission information (1103). The CPU 101 creates a bar code 1203 corresponding to the re-transmission information (1104), adds the bar code 1203 to a transmission error message 1205 outputted to inform the user of the transmission error, and prints out the transmission error message 1205 onto a sheet of paper through the image printer 112 so that it is discharged as a transmission error report sheet 1204 (1105). The transmission error report sheet 1204 corresponds to a medium of the present invention.

Then, when the user intends to perform re-transmission (1106), the transmission error report sheet 1204 having the bar code is set on the image reader 110 and the printed portion is read in (1107). The CPU 101 cuts out the bar code 1203 from the image information being read in and decrypts the bar code 1203 (1108) to thereby obtain re-transmission information corresponding to the bar code 1203 (1109). The CPU 101 sets transmission conditions at the facsimile transmitter 116 and performs facsimile re-transmission (1110). Thus, the user can perform facsimile re-transmission simply by performing a simple operation such that the transmission error report sheet 1204 is read in without any need to re-type the receiver's facsimile number or search for image information. Since a device such as a display is unnecessary which is necessary if the search for image information is performed, the price of the apparatus is reduced. An example of the transmission error report sheet 1204 is shown in FIG. 9.

While the identification information of the present invention is the storage location information in the above-described embodiments, any information such as an ID may be used that enables the identification of a desired electronic document file.

Needless to say, the electronic document file data of the present invention are not necessarily inputted through a facsimile.

While in the above-described embodiments, the image information communication apparatus of the present invention is described with respect to the case where the image information processor includes the function of the image information communication apparatus, the present invention is not limited thereto. The following arrangement, for example, may be used:

The image information communication apparatus may include a facsimile communication means for transmitting and receiving image information according to the facsimile format, a re-transmission information generating means for, when a transmission error occurs during the transmission according to the facsimile format, generating, together with a transmission error message, re-transmission information including receiver information

for identifying the receiver of the facsimile transmission and information for identifying the image information whose transmission resulted in error, and a re-transmission control means for, when re-transmission according to the facsimile format is directed, causing the facsimile communication means to re-transmit the image information whose transmission resulted in error by use of the generated re-transmission information. The image information transmitter may be arranged to further include, in addition to the above-described means, a transmission error message outputting means for outputting the re-transmission information generated by the re-transmission information generating means and the error message so as to be shown on the same medium and so that the medium being outputted is set, the re-transmission information is read out from the medium being set and the re-transmission information being read out is used for the re-transmission by the facsimile communication means. Thus, even if a transmission error occurs during the facsimile transmission and re-transmission is necessitated, the facsimile re-transmission is easily performed simply by performing a simple operation such that the medium being outputted is set and read in.

Moreover, the operations of means of the above-described embodiments may be realized by means of software by the working of a program with a computer. Alternately, the operations may be realized by means of hardware with a particular circuit arrangement without the use of the computer.

As described above, according to the present invention, the identification of an electronic document file in the memory unit may easily be performed simply by reading in a printed output corresponding to the electronic document file without any need to display the electronic document file on the display unit for successive search.

Since the display unit for displaying the result of the successive search is unnecessary, the cost is reduced.

Since an attached document may be facsimile-transmitted simply by reading it in together, the procedure to attach a facsimile transmission document is simplified.

In the case where the inputted use permission information is collated with the previously-recorded use permission information and the facsimile-received document is printed out only when both of the information coincide with each other, since persons not permitted to use the apparatus and not having the use permission information cannot take out the facsimile-received document even if they perform reading-in of the superimposed image with the intention to take out the facsimile-received document, a highly reliable simple confidential reception function is realized.

Additionally, even if a transmission error occurs during the facsimile transmission and re-transmission is necessitated, the facsimile re-transmission may be performed simply by performing a simple operation such

that a transmission error report having a bar code corresponding to the re-transmission information is set and read in.

## 5 Claims

### 1. An image information processor comprising:

storage means for storing a plurality of electronic document files;  
image superimposing and outputting means for superimposing identification information for identifying a predetermined electronic document file stored in the storage means on image information of a specific page of the predetermined electronic document file, and printing out the superimposed image; and  
readout means for reading a printed output of the superimposed image, reading the identification information included in the superimposed image, and reading a corresponding electronic document file from the storage means based on the file identification information,

wherein when an attached document is read in together with the printed output of the superimposed image, the readout means makes a distinction between the printed output of the superimposed image and the attached document by use of the identification information.

### 2. An image information processor according to claim 1, further comprising facsimile transmission means for facsimile-transmitting to the same receiver both of the electronic document being read out and the attached document being read in.

### 3. An image information processor according to claim 1, wherein said identification information is a bar code or a character string.

### 4. An image information processor comprising:

storage means for storing a plurality of electronic document files;  
image superimposing and outputting means for superimposing identification information for identifying a predetermined electronic document file stored in the storage means on image information of a specific page of the predetermined electronic document file, and printing out the superimposed image;  
readout means for reading a printed output of the superimposed image, reading the identification information included in the superimposed image, and reading a corresponding electronic document file from the storage

- means based on the file identification information; and  
 facsimile reception means for receiving data transmitted from a facsimile,  
 wherein the plurality of electronic document files stored in the storage means include a file received by the facsimile reception means.
5. An image information processor according to claim 4, wherein said readout means collates input password information being inputted with previously-recorded use permission information, and reads out an electronic document file stored through the facsimile reception means only when both of the information coincide with each other.
6. An image information processor comprising:  
 storage means for storing a plurality of electronic document files;  
 image superimposing and outputting means for superimposing identification information for identifying a predetermined electronic document file stored in the storage means on image information of a specific page of the predetermined electronic document file, and printing out the superimposed image; and  
 readout means for reading a printed output of the superimposed image, reading the identification information included in the superimposed image, and reading a corresponding electronic document file from the storage means based on the file identification information,  
 wherein said readout means collates input password information being inputted with previously-recorded use permission information, and reads out an electronic document file being stored only when both of the information coincide with each other.
7. An image information processor according to claim 5 or 6, wherein said input password information is stored on a magnetic card, and the input password information is read out from the magnetic card and transmitted to the readout means, said magnetic card being inserted into a magnetic card reader.
8. An image information processor according to claim 5 or 6, wherein said input password information is stored on an IC card, and the input password information is read out from the IC card and transmitted to the readout means, said IC card being inserted into an IC card reader.
9. An image information processor according to claim 1, 4 or 6, wherein the superimposed image is printed out immediately after the electronic document file is stored in the storage means.
10. An image information processor according to any of claims 1 to 9, wherein said identification information is information on a storage location of the electronic document file in the storage means.
11. An image information processor according to any of claims 1 to 10, wherein said specific page is the first page.
12. An image information processor comprising:  
 storage means for storing a plurality of electronic document files;  
 image superimposing and outputting means for superimposing identification information for identifying a predetermined electronic document file stored in the storage means on image information of a specific page of the predetermined electronic document file, and printing out the superimposed image;  
 readout means for reading a printed output where the superimposed image is shown, reading the identification information included in the superimposed image, and reading a corresponding electronic document file from the storage means based on the file identification information;  
 facsimile communication means for transmitting and receiving according to a facsimile format the electronic document file read out by the readout means;  
 transmission error message generating and outputting means for adding at least receiver information for identifying a receiver of an electronic document file whose transmission resulted in error and identification information for identifying the electronic document file to a medium on which a transmission error message is shown, said medium being outputted when a transmission error occurs during transmission according to the facsimile format; and  
 re-transmission control means for, when re-transmission according to the facsimile format is directed, causing the facsimile communication means to re-transmit the electronic document file whose transmission resulted in error by using at least the receiver information and the identification information added to the medium being outputted.
13. An image information processor according to claim 12, wherein said medium being output is set, the receiver information and the identification information are read from the medium being set, and the information being read is used in the re-transmission.



sion by the facsimile communication means.

14. An image information communication apparatus comprising:

5

facsimile communication means for transmitting and receiving image information according to a facsimile format;

re-transmission information generating means for, when a transmission error occurs during transmission according to the facsimile format, generating, together with a transmission error message, re-transmission information including receiver information for identifying a receiver of the facsimile transmission and information for identifying image information whose transmission resulted in error; and

10

15

re-transmission control means for, when re-transmission according to the facsimile format is directed, causing the facsimile communication means to re-transmit the image information whose transmission resulted in error by using the re-transmission information being generated.

20

25

15. An image information communication apparatus according to claim 14, further comprising transmission error message outputting means for outputting the re-transmission information and the error message generated by the re-transmission information generating means so as to be shown on the same medium,

30

wherein said medium being output is set, the re-transmission information is read from the medium being set, and the re-transmission information being read is used in the re-transmission by the facsimile communication means.

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5A




FIG. 5B






FIG. 6




	
<u>Published Unexamined Patent Application</u>	
<hr/>	
	

FIG. 7



<u>Facsimile Cover Sheet</u>
<u>To: Mr. Tanaka, ... Co., Ltd.</u>
<u>From: Suzuki, ... Co., Ltd.</u>
<div>Message</div>

FIG. 8




FIG. 9

1204

Transmission Error Report

1205

Please read in this report when performing re-transmission.  
Re-transmission will be performed automatically.

1201

Receiver's Facsimile Number  
03-5000-1111

1202

Date of Transmission  
May 3, 1994 12:30

1203

1205

1205

FIG. 10 PRIOR ART




FIG. 11 PRIOR ART






FIG. 12 PRIOR ART





Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 0 817 461 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
16.08.2000 Bulletin 2000/33

(51) Int. Cl.<sup>7</sup>: G06F 17/30, H04N 1/21

(43) Date of publication A2:  
07.01.1998 Bulletin 1998/02

(21) Application number: 97110402.1

(22) Date of filing: 25.06.1997

(84) Designated Contracting States:  
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE

(30) Priority: 25.06.1996 JP 16401696

(71) Applicant:  
MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.  
Kadoma-shi, Osaka-fu, 571 (JP)

(72) Inventors:  
• Hisatomi, Kenji  
Moriguchi-shi, Osaka 570 (JP)

• Yamaguchi, Takehito  
Hirakata-shi, Osaka 573 (JP)  
• Murata, Kazuyuki  
Kyotanabe-shi, Kyoto 610-03 (JP)  
• Matsukawa, Shigeru  
Hirakata-shi, Osaka 573 (JP)


(74) Representative:  
Grünecker, Kinkeldey,  
Stockmair & Schwanhäusser  
Anwaltssozietät  
Maximilianstrasse 58  
80538 München (DE)

(54) Image Information processor and Image Information transmitter

(57) An image information processor has an image superimposing and outputting means for printing out a superimposed image where a bar code representative of a storage location of an electronic document file received through a facsimile is superimposed on the first page of the electronic document file. When a necessary electronic document file is read out, the bar code is read from the printed output corresponding to the

necessary electronic document file being set by the user, the storage location of the electronic document file is decrypted from the bar code to thereby identify and read out the electronic document file. In this case, the reading of the bar code is performed only when a permitted password is inputted by the user. The readout of the electronic document file is not performed otherwise.

FIG. 1



EP 0 817 461 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 97 11 0402

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cls)
X A	EP 0 621 721 A (XEROX CORP) 26 October 1994 (1994-10-26) * abstract * * page 3, line 34 - page 5, line 17 * * page 6, line 49 - page 6, line 54 *	1,3,4, 9-11 12,13	G06F17/30 H04N1/21
X A A	EP 0 435 254 A (TOKYO SHIBAURA ELECTRIC CO) 3 July 1991 (1991-07-03) * column 1, line 29 - column 1, line 50 * * column 43, line 3 - column 43, line 18 * * column 24, line 19 - column 24, line 34 *	1,3,9-11 12,13 5-8	
P,X	EP 0 751 672 A (MATSUSHITA ELECTRIC IND CO LTD) 2 January 1997 (1997-01-02) * column 2, line 50 - column 6, line 57; claims 11-13,16,17 * * column 9, line 25 - column 10, line 15 *	1,4	
X	EP 0 531 062 A (CANON KK) 10 March 1993 (1993-03-10) * column 1, line 11 - column 1, line 22 * * column 3, line 2 - column 3, line 10; claims 1-8; figure 2 *	14,15	TECHNICAL FIELDS SEARCHED (Int.Cls)
A	US 4 591 921 A (NAKAJIMA TOSHIFUMI) 27 May 1986 (1986-05-27) * column 3, line 32 - column 4, line 20 *	12-15	G06F H04N
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>17 May 2000</b>	Examiner <b>Correia Martins, F</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</p> <p>T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons</p> <p>***** &amp;: member of the same patent family, corresponding document</p>			

EPC FORM 1503 (03.02) (P04C01)



European Patent  
Office

Application Number  
EP 97 11 0402

### CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

### LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☒ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:





European Patent  
Office

**LACK OF UNITY OF INVENTION  
SHEET B**

Application Number  
EP 97 11 0402

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

**1. Claims: 1-11**

facsimile transmission system for transmitting both a stored document requested by a registration sheet and an attached document.

**2. Claims: 12-15**

Facsimile transmission system for easy recover of transmission errors by using re-transmission identification means to resend previous data.

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 11 0402

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-05-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0621721 A	26-10-1994	BR 9401558 A	01-11-1994
		CA 2121848 A	23-10-1994
		JP 7021214 A	24-01-1995
		US 5682540 A	28-10-1997
EP 0435254 A	03-07-1991	JP 3196266 A	27-08-1991
		DE 69017629 D	13-04-1995
		DE 69017629 T	29-06-1995
		US 5548666 A	20-08-1996
		US 5222157 A	22-06-1993
EP 0751672 A	02-01-1997	US 5754308 A	19-05-1998
		CA 2178133 A	28-12-1996
		JP 9037004 A	07-02-1997
EP 0531062 A	10-03-1993	JP 5068150 A	19-03-1993
		DE 69220738 D	14-08-1997
		DE 69220738 T	06-11-1997
		US 5335085 A	02-08-1994
US 4591921 A	27-05-1986	JP 4010782 B	26-02-1992
		JP 59027673 A	14-02-1984
		DE 3327905 A	09-02-1984

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**